



## MagnaPrint® Flockbinder NG

### Electrostatic flock adhesive

MagnaPrint® Flockbinder NG is a specially formulated adhesive for all types of flock fibres.

MagnaPrint® Flockbinder NG is a fully aqueous ready to use adhesive, it should be printed immediately prior to the flock applicator.

### Application

MagnaPrint® Flockbinder NG requires the addition of 1 - 2% MagnaPrint® Crosslinker 200 when used for panel printing.

Printing should occur through a 34 - 43T (86 - 110) mesh and after flocking the print should be fixed under normal pigment printing conditions 2½ - 3 minutes at 165°C (330°F).

If required, when using white flock, MagnaPrint® Flockbinder NG can be tinted with up to 4% pigment to give a melange type effect or pastel multicolour designs.

The excellent adhesive properties of MagnaPrint® Flockbinder NG make it also suitable for use as a base for flock / glitter combinations.

### SPECIFICATION



#### FABRIC TYPES

Cotton / Poly Cotton blends



#### MESH

34 - 43T (86 - 110)



#### SQUEEGEE

Medium 65° Shore  
Rectangular



#### STENCIL

Water resistant emulsion



#### CURE TEMPERATURE

2½ - 3 Minutes at 165°C  
(330°F)



#### PIGMENT LOADING

Up to 4% MagnaPrint®  
Eco Pigments



#### ADDITIVES

Crosslinker 200



#### STORAGE

In cool place properly closed:  
>5°C (40°F) <25°C (77°F)



#### HEALTH & SAFETY

MSDS available upon  
request



#### CLEAN UP

Wash off screen using water  
and mild detergent

All information is given in good faith but without warranty. They do not release you from testing our products as to their suitability for the intended processes and uses.